Claims

1. A recording medium used for storing data, comprising adigital stream generated by multiplexing a video stream and a graphics stream, wherein:

the graphics stream is a sequence of a plurality of packets which include a packet containing control information; and

the control information indicates that graphics data contained in a preceding packet in the sequence is to be displayed at a predetermined time in a state of being overlaid on the video stream.

2. The recording medium of Claim 1, wherein:

5

each of the plurality of packets belongs to any of a plurality of display sets which are each used for producing a graphics display;

the graphics data and the control information belong to different display sets; and

the graphics data is non-referenced graphics data that is not referenced by control information which belongs to a same display set as the non-referenced graphics data.

3. The recording medium of Claim 1, wherein:

the control information is completely contained within the packet; and

the predetermined time is shown by a time stamp written in the packet.

4. The recording medium of Claim 1, wherein:

the graphics stream includes palette data in combination with the control information; and

the control information indicates that the graphics data is to be color-converted using the palette data.

5. The recording medium of Claim 4, wherein:

the display indicated by the control information is to update a previous display of the graphics data;

the control information has an update flag; and the update flag shows whether the update is to be performed using only the palette data.

15 6. The recording medium of Claim 1, wherein:

20

the graphics stream includes window information;
the window information specifies a position, a height,
and a width of a window on a screen, the window being an area
in which the graphics data is to be rendered when overlaying
the graphics data on the video stream; and

the control information indicates that the graphics data is to be positioned within the window.

7. A reproduction apparatus for reproducing a digital stream 25 generated by multiplexing a video stream and a graphics stream, comprising:

a video decoder operable to decode the video stream to generate a moving picture; and

a graphics decoder operable to decode the graphics stream to generate graphics, and overlay the graphics and the moving picture, wherein

upon reading control information in the graphics stream, the graphics decoder displays graphics which has been generated by decoding graphics data that precedes the control information in the graphics stream, based on the control information.

10 8. The reproduction apparatus of Claim 7, wherein:

the graphics stream includes a plurality of display sets each of which is used for producing a graphics display;

the graphics data is non-referenced graphics data that is not referenced by control information which belongs to a same display set as the non-referenced graphics data; and

upon reading the display set to which the non-referenced graphics data belongs, the graphics decoder decodes the non-referenced graphics data to generate the graphics and stores the generated graphics to an object buffer.

20

15

9. The reproduction apparatus of Claim 7, wherein:

the control information is completely contained within one packet; and

the graphics decoder displays the graphics at a time,
on a reproduction time axis of the video stream, that is shown
by a time stamp written in the packet.

10. The reproduction apparatus of Claim 7, wherein:

the graphics generated by decoding the graphics data is expressed using a code value;

the reproduction apparatus further comprises
a lookup table unit operable to convert the code value
to a pixel value;

5

10

the graphics stream includes palette data in combination with the control information; and

the graphics decoder sets the palette data in the lookup table unit and instructs the lookup table unit to convert the code value to the pixel value using the palette data.

11. The reproduction apparatus of Claim 10, wherein:

the display performed by the graphics decoder is to update a previous display of the graphics;

the control information has an update flag; and if the update flag shows a predetermined value, the graphics decoder updates the previous display of the graphics by setting the palette data in the lookup table unit.

20 12. The reproduction apparatus of Claim 7, wherein:

the graphics stream includes window information;

the window information specifies a part of a screen as a graphics display window; and

the graphics decoder displays the graphics by clearing
the window specified by the window information and writing
the graphics into the window.

13. A method of recording onto a recording medium, comprising

the steps of:

generating application data; and recording the application data to the recording medium,

wherein:

25

5 the application data includes a digital stream generated by multiplexing a video stream and a graphics stream;

the graphics stream is a sequence of a plurality of packets which include a packet containing control information; and

the control information indicates that graphics data contained in a preceding packet in the sequence is to be displayed at a predetermined time in a state of being overlaid on the video stream.

15 14. A computer-readable program used in a computer for reproducing a digital stream generated by multiplexing a video stream and a graphics stream, comprising:

program code operable to cause the computer to decode the video stream to generate a moving picture; and

program code operable to cause the computer to decode the graphics stream to generate graphics, and overlay the graphics and the moving picture, wherein

upon reading control information in the graphics stream, graphics which has been generated by decoding graphics data that precedes the control information in the graphics stream is displayed based on the control information.

15. A method of reproducing a digital stream generated by

multiplexing a video stream and a graphics stream, comprising the steps of:

decoding the video stream to generate a moving picture; and

decoding the graphics stream to generate graphics, and overlaying the graphics and the moving picture, wherein

5

10

upon reading control information in the graphics stream, the step of decoding the graphics stream displays graphics which has been generated by decoding graphics data that precedes the control information in the graphics stream, based on the control information.